

$0.01C_{RUR}$ or $0.5\mu A$ whichever is greater
 (85°C): $10 \cdot 0.08C_{RUR}$ (μA)
 (125°C): $10 \cdot 0.1C_{RUR}$ (μA)

Dissipation factor (20°C): see table 1

Table 1

Capacitance (μF)	Cap. Change C/C %			MAX.					
	-55°C	+85°C	+125°C	DF(%)Max				DCL Max.	
				-55°C	+20°C	+85°C	+125°C	+85°C	+125°C
1	±8	±8	±10	3	3	3		8 10	10 10
1.5 68				5	5	5			
100 330				6	6	6			
470 1000				8	8	8			

Note 1 Measured at a voltage derating.

3, Drawing , Dimensions and Max Weight

Table 2

Case code	Weight Max g	uninsulated		With insulated sleeve		d±0.1 mm
		D±0.5 mm	L±2 (mm)	D±0.5 mm	L±2 (mm)	
1	0.7	3.2	8	4	10	0.4
2	2.3	5	12	5.8	14	0.6
3	3.0	6	14	6.8	16	0.6
4	4.0	8	14	8.8	16	0.8
5	8.0	8	22	8.8	24	0.8
6	14.0	10	22	10.8	24	0.8

Note: When encapsulated with plastic insulation sleeve, dimension D increase 0.8mm and L increase 2mm.



4, Nominal Capacitance, Rated voltage, Voltage Derating

Table 3

Rated voltage	6.3	10	16	25	32	40	63	75	100
Voltage Derating									



Shanghai Green Tech Co.,Ltd.

GTCAP